

ELECTRIC PATTERN
SEWING MACHINE

电脑花样机

高效美观的缝制效果，缝制范围更广、适应性更强，使用节能技术，机器更节能，更环保。

Highly active, pleasing to the eyes sewing effects, more large sewing area, more stronger practise, saving energy, more environmental protection.



CC-3020G-01A

缝制范围：300x200mm

使用两步下降的大压脚轻松定位布料,视野宽阔清晰可见,由于未安装压脚臂支撑板,从而使视野宽阔清晰可见,同时使缝纫检查和面料定位也更简单。

Two steps down big presser ,easy fix fabric.More clearly range of vision.Never fix pressingarm support board ,the range of vision become more clearly.The sewing check and positioning fabric have been used at the same time,it is become very easy.



缝制实例



规格 Specification

型号Model	CC-3020G-01A
线迹型式Line	单针平缝Single-needle flat seam
最高缝纫速度Highest sewing speed	2,700 rpm
缝制区域(X × Y) Sewing area	300×200 mm
送布装置 Cloth feeding device	间歇送布 (脉冲马达驱动) Intermittent feeding (driven by pulse motor)
针距 Stitch length	0.05 - 12.7mm
最大针数Max. needle number	20,000针/1个图案(20,000 needles/1 pattern)
压脚驱动方式 Foot presser driving mode	气动 Pneumatic
压脚高度 Work Clamp Height	最大Max. 30 mm
两步压脚2-step presser foot	分离式压脚 Divided presser foot
间歇压脚上升量 Rising amount of intermittent foot presser	22 mm
间歇压脚行程 Stroke by intermittent presser foot	0或2 - 10 mm (出厂设置: 3mm) 0 or 2 - 10 mm (Factory defaults: 3mm)
旋梭Hook	两倍摆梭 Double Shuttle Hook
扫线装置 Scavenging device	标准装备 Standard facility
切线装置 Cutting device	标准装备 Standard facility
夹线器 Tension device	电子夹线器 Elctric tension device
数据存储方式 Data storage way	USB或闪存 (使用CF卡可任意缝纫图案) USB or Flash memory (You can sew pattern with CF card)
马达 Motor	AC伺服马达550W AC servomotor 550W
重量 Weight	机头: 约135 kg 操作盘: 约0.6 kg 控制箱: 14.2 - 16.2 kg(根据出口国家不同) Head: about 135 kg Operating panel: about 0.6 kg control box: 14.2 - 16.2 kg (according to different export countries)
电源 Power	单相220V Single phase 220V 三相Three-phase 380V
气压 Air pressure	0.5 Mpa 1.8 L/min
净重/N.W	220
毛重/G.W	290
包装尺寸/Measurement	1260*1260*1350
体积/CBM	2.14m³